

SFU	SWITCH DISCONNECTOR FUSE UNITS 32A TO 800A confirms to IEC IS 13947 (Pt-3), IEC 60947-3 (Fuse Extra)								HRC FUSE LINKS Rate Per Unit				
	SDF RATING	FN-Interior (Open)	Suitable HRC Fuses	FN in SS Encl (with Box)	Capacitor Duty Contactors - Type MOC		CHANGEOVER SWITCHES (TPN) Type C-LINE		FUSE BASE	RATING AMPS.	TYPE HF		
32A	2300	HF	5240	SIZE	RATE			Open Exec.	SS ENCL.	2 to 32A HF	2-32A	122.00	
63A	3200	HF	6260	MO C3	1835			4940	7410	185	40A	135.00	
100A	6230	HNOO	10180	MO C5	1920			6570	9450	2 to 63A HF	50A	288.00	
125A	8310	HNOO	12030	MO C8.5	2155			10320	11790	205	63A	350.00	
160A	8860	HNOO	12880	MO C10	2340			10860	15370	DIN TYPE FUSE LINKS TYPE HN			
200A	11260	HNO	17650	MO C12.5	2405			13180	17770	(FN 100/125/160 A)		SIZE - HN 00	
250A	13290	HNI	19930	MO C15	3225			19070	24700	RATING AMPS.		RATE	
315A	16370	HNI	23020	MO C20	3655			19870	25890	63 A		480.00	
400A	19800	HNII	26150	MO C25	4135			29320	37740	80 / 100 A		480.00	
630A	31880	HN III	42290	MO C30	6495			34370	43740	125 A		510.00	
800A	34580	HN III	45180	MO C40	11240			48910	71500	160 A		515.00	
1000A				MO C50	11725			86520	114640				
1250A				MO C60	13615			115460		(FN 200 A)		SIZE - HN 0	
1600A				MO C75	15710			136540		80 / 100 / 125 A		675.00	
2000A				MO C85	17270			196540		160 A / 200 A		685.00	
2500A				MO C100	18645								
3150A										(FN 250 -315 A)		SIZE - HN I	
MOTOR STARTERS STAR DELTA										125 A		690.00	
DOL	DIRECT ON-LINE STAR IN SS ENCL.				STAR DELTA		FULLY/SEMI AUTOMATIC				160		700.00
MAX MOTOR OP at 415, 3Ph		RELAY MAX RANGE	DESC RIPTION	RATE PER UNIT	MAX MOTOR OP at 415,		RELAY MAX (A)	RATE PER UNIT		200A		705.00	
HP	KW				HP	KW		TYPE	FASD	SASD	250 A	790.00	
3.0	2.5	12-20	MF1 1Phase		12.5	9.3	9-14	MK-1			315 A	960.00	
7.5	5.5	11-18	MF1 3 Phase		15.0	11.0	11-18	MK-1			(FN 400 A)		
Upto7.5	5.5	upto 9-14	MK1 DOL		15.0	11.0	13-22	MK-1			200 A	990.00	
7.5	5.5	11-18	MK1 DOL		25.0	18.5	13-21	ML-1.5			250 A	995.00	
7.5	5.5	13-22	MK1 DOL		35.0	26.0	20-32	ML-2			315 A	1040.00	
7.5	5.5	20-32	MK2 DOL		50.0	37.5	28-42	ML-3	52330		400 A	1070.00	
DOL	Direct ON-Line Star with SPP in SS Encl				75.0	55.0	45-75	ML-4	89685		(FN 630/800 A)		
					125.0	90.0	66-110	ML-6	147045		315 A	1500.00	
10.0	7.5	9-15	MN-16 DOL	4185							400 A	1580.00	
											500 A	1690.00	
15.0	11	14-23	MN-25 DOL	6400	MN Fully Automatic STAR DELTA WITH SPP							630 A	1770.00
					17.5	13.0	9-15	MN-16	14100		800 A	2190.00	
					30.0	22.5	14-23	MN-25	15765		TERMS & CONDITIONS :		
20.0	15	20-33	MN-32 DOL	10325	40.0	30.0	20-33	MN-32	25940		1) + GST Extra as applicable		
30.0	22.5	30-50	MN-45 DOL	17665	50.0	37.0	30-50	MN-45	41660		2) P&F Extra		
45.0	33.5	45-75	MN-65 DOL	24185	75.0	55.0	45-75	MN-65	69030		3) W.E.F 1 ST NOV 2019		
15.0	11	20-32	ML-1.5 DOL		90.0	67.0	45-75	MN-80	75455		4) This price list is subject to change without any prior notice.		
20.0	15	20-32	ML-2 DOL		150.0	110.0	66-110	MN-110	98770				
30	22.5	28-42	ML-3 DOL	21705	180.0	130.0	90-150	MN-140	103385		5) This cancels all our previous price lists.		

w.e.f 1st July-2021

										w.e.f 1st July-2021			
MCCB's	MOULDED CASE CIRCUIT BREAKERS CONFIRMING TO IS 13947 (PART-2)										TIMER & TIME SWITCHES		
RATING AMP'S	DU 100D 18KA		DU 100H 30KA		DU 250 C 25KA			DU 250 36KA					
	3 POLE	4 POLE	3 POLE	4 POLE	RATINGS AMP	3 POLE	4 POLE	3 POLE	4 POLE	GIC FM/1 QT BASE MTG/W			
63 A	4280	5510	4620	6360	160 A	7480	9630	8310	10110				
100 A	4280	5510	4620	6360	200 A	8910	11380	10770	13890	GIC 2ASD TO TIMER			
125 A	4970	6470	5480	7030	250 A	9810	12890	12370	15920				
	DY-125U 10KA 3 POLE		DY-125U 10KA 4 POLE		320 A DU400N 50 kA			17400	21450	SPREADER TERMINAL			
63 A	1960	2610			400 A DU400N 50 Ka			17400	21450	ITEM	3 POLE	4 POLE	
100 A	2150	2990								DN1/DN2 250	1460	1920	
125 A	3180	3960								DN3 400	2760	3955	
										DN3 630	3190	4300	
D-SINE MCCB's Thermal Magnetic Release		(36 KA) TYPE - S		(50 KA) TYPE - H		ROTARY OPERATING MECHANISM (HANDLE)							
		STD Breaking Capacity		High BreakingCapaci		TYPE		DIRECT HANDLE		NEW EXTENDED		DN 2 & DN 3	
TYPE	RANGE	3 POLE	4 POLE	3 POLE	4 POLE	DY 125U		1050.00		1685.00		DN2 DIRECT 1230	
DN2-250	100-125	12650	15780	18460	22050	DU 100D / DU 125D / DU 100H / DU 125H		1145.00		1500.00		DN2 Extended 1720	
	125-160	16680	19990	20930	25270	DU 250/250C		1190.00		1675.00			
	160-200	19740	26130	22000	29990	SPREADER		3 POLE		4 POLE		DN3 DIRECT 1845	
	200-250	22160	27450	23800	30730	DY 125U		330.00		520.00		DN3 Extended 3170	
DN3-400	250-320	26970	32610	29400	36050	DU 100D / DU 100H		330.00		520.00			
	320-400	26970	32610	29400	36050	DU 125D / DU 125H		430.00		620.00			
DN3-630	400-500	37480	46290	40260	50740	DU 250C / DU 250		1460.00		1920.00			
	500-630	37480	46290	40260	50740								