

LED Pilot Light Ø 16.5 plastic construction

MRP with effect from 01.11.2021



General Characteristics:

This range of LED Monoblock Pilot Light Ø 16.5 is available in round & square head in a variety of colours. This Pilot Light can be fixed in any position on panels of thickness varying from 1 mm to 6 mm. The pilot light is fastened to the panel with a lock ring. We recommend min fixing centres of 25 mm x 25 mm.

Pilot lights are available with integral LED's suitable for operating at various voltages, namely 6 V, 12 V, 24 V, 30 V, 48 V, 63 V, 110 V, 125 V & 240 V AC / DC.

Electrical and mechanical characteristics


A) Mechanical Characteristics

Applicable Standard	UL 508 IEC 60947-5-1 CSA 22.2
Degree Of Protection	IP 65 (as per IEC 60529) Dust & water tight
Operating Conditions	+ 70° C to -25° C
Contact Material	Brass (tin plated)
Corrosion Protection	All metallic parts are electroplated for corrosion protection
Terminal Torque	0.5 Nm
Viewing Angle	More than 100°
Optical Axial intensity	More than 100 mcd for all colors





































B) Electrical Characteristics

Rating	Rated 6 VAC, DC, 12 VAC, DC, 24 VAC, DC, 110 VAC, 110 VDC, 240 VAC & 220 VDC	
Terminal Capacity	Rigid	Flexible
	2 X 0.75 mm ² (max)	1 X 0.75 mm ² (max)
	1 X 0.5 mm ² (min)	1 X 0.5 mm ² (min)
	1 X 1.5 mm ² (min)	2 X 0.5 mm ² (mix)
Dielectric Test	2.5 kV	
Rated Insulation Voltage	500 V DC	
Polarity Protection	Nil	
Low Voltage Protection	20% of Rated Voltage	
Current Consumption	Max. 20 mA for AC Circuits	
	Max. 15 mA for DC Circuits	

16.5 Ø - PILOT LIGHTS WITH INTEGRAL LED



SPECIFIC VOLTAGE


VOLTAGE	COLOUR	ORDERING CODE	COLOUR	ORDERING CODE	COLOUR	ORDERING CODE	COLOUR	ORDERING CODE	COLOUR	ORDERING CODE
12 A C/DC		6PLBR1L (S)12		6PLBR3L12		6PLBR4L12		6PLBR5L12		6PLBR6L12
		6PLBR7L(S)12		6PLBR8L12	 Translucent Lens / White LED		 Transparent Lens / White LED			
24 A C/DC		6PLBR1L (S)24		6PLBR3L24		6PLBR4L24		6PLBR5L24		6PLBR6L24
		6PLBR7L(S)24		6PLBR8L24	 Translucent Lens / White LED		 Transparent Lens / White LED			
110 AC		6PLBR1L(S)110AC		6PLBR3L110AC		6PLBR4L110AC		6PLBR5L110AC		6PLBR6L110AC
		6PLBR7L(S)110AC		6PLBR8L110AC	 Translucent Lens / White LED		 Transparent Lens / White LED			
240 AC		6PLBR1L(S)240AC		6PLBR3L240AC		6PLBR4L240AC		6PLBR5L240AC		6PLBR6L240AC
		6PLBR7L(S)240AC		6PLBR8L240AC	 Translucent Lens / White LED		 Transparent Lens / White LED			

Note: Other voltages namely 6 V, 30 V, 48 V available on request

PRICE LIST w.e.f. 01.11.2021

**Control & Signalling Devices 16.5 Ø
PLASTIC SERIES**

LED PILOT LIGHTS ECONOMY SERIES

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs.	
	Integral LED	White LED / White Lens	6PLBR1L(S)	261.00	
	6V, 12V, 24V, 48V AC/DC	Green LED / Green Lens	6PLBR3L	113.50	
	110VAC, 230VAC	Red LED / Red Lens	6PLBR4L	113.50	
		Amber LED / Amber Lens	6PLBR5L	113.50	
		Blue LED / Blue Lens	6PLBR6L	336.00	
		White LED / Clear Lens	6PLBR7L(S)	261.00	
		Yellow LED / Yellow Lens	6PLBR8L	113.50	
	Please mention the voltage required after the ordering code				

GENERAL TERMS AND CONDITIONS

General Terms : Prices are ex-works Mumbai
 HSN CODE : 85365010 for all the products of this MRP List
 GST : 18%

Prices are subject to revision without notice and ruling at the time of delivery.

This price list supersedes all previous Price Lists.

Warranty Policy : TEKNIC equipment is guaranteed under the following terms:

For a period of 12 months from the date of sale, TEKNIC guarantees that its products are free from defects in material and workmanship, with the exception of consumables rendered unserviceable through normal use. During the said period, TEKNIC will replace or repair all parts acknowledged as defective due to factory workmanship and which have been returned in a timely manner by Buyer to TEKNIC and all costs and duties paid, together with a detailed description of the failure and a certified declaration of the number of hours of operation. Repaired or replaced parts will be redelivered FCA (named place) as per INCOTERMS 2000. This warranty is subject to the provision of correct usage, proper maintenance and does not cover defects arising out of fire, faulty operation, accident, inefficient maintenance and wilful or accidental damage.

TEKNIC guarantee applies to all equipment, parts and components stored, installed, protected, maintained and used in accordance with TEKNIC specifications and instructions, and respecting the rules for normal use, without any modification by Buyer.

All other conditions or warranties, whether express or implied, relating to the quality and operation of the equipment are excluded, as well as any liability for loss or damage caused directly or indirectly by the equipment or resulting from its use.

Proof of purchase to be provided to avail warranty.

TEKNIC ELECTRIC (I) PVT. LTD.

Reg. Office : 116, Hammersmith Industrial Estate, Mahim (W), Mumbai – 400016.
 Head Office : 703/704/705, Madhava, Bandra Kurla Complex, Bandra (E), Mumbai – 400051. Tel : +91-22-42532500
 Works : 65, Marol Co-op. Industrial Estate Ltd., M. Vassanji Road, Andheri (East), Mumbai – 400059. Tel : +91-22-42534500
 Email : teknic@teknico.in mfg@teknico.in Website : www.teknico.in